

# ZOCHEM INC.

A SUBSIDIARY OF HORSEHEAD HOLDING CORP.

P.O. BOX 1120  
BRAMPTON, ONTARIO, CANADA L6V 2L8

PH: 800 324-1806  
PH: 905 453-4100

<b>ZOCO 102</b>	<b>ZOCHEM ZINC OXIDE</b>
-----------------	--------------------------

<b>FRENCH PROCESS ZINC OXIDE</b>
<b>PRODUCED FROM PRIMARY GRADE ZINC</b>

<b>DESCRIPTION</b>
--------------------

ZOCO 102 is a fine particle size, high purity, zinc oxide excellent for applications requiring high reactivity and good suspension.

<b>USES</b>
-------------

Rubber, Paint, Chemicals, Stearates, Resins, Primers, Adhesives

### TYPICAL TECHNICAL VALUES\*\*

<b>CHEMICAL PROPERTIES (%)</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Zinc Oxide (ignited basis)		99.9	99.9
Lead (Pb)	0.0024		0.0015
Cadmium (Cd)	0.0010		0.0003
Copper (Cu)	0.0005		0.0001
Iron (Fe)	0.0005		0.0002
Loss at 100 C	0.15		0.05

  

<b>PHYSICAL PROPERTIES</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Surface Area (m <sup>2</sup> /g)	11.00	8.00	10.00
Particle Size (microns)	0.13	0.11	0.12
Bulk Density (lb/cu. ft)			43
Apparent Density (lb/cu. ft)			16.0
Screen Test - Through 325 Mesh (%)		99.95	99.980
Specifications			ASTM D-79

\*\* The above specifications are typical for the noted grade. Zochem will produce material to meet specific customer specifications.

REVISION 10: November 4 2011