



**ZOCHEM INC.**

A SUBSIDIARY OF HUDBAY MINERALS INC.

P.O. BOX 1120  
BRAMPTON, ONTARIO, CANADA L6V 2L8

PH: 800 324-1806  
PH: 905 453-4100

**ZOCO 104P** **ZOCHEM ZINC OXIDE**

**FRENCH PROCESS ZINC OXIDE  
PRODUCED FROM SPECIAL HIGH GRADE ZINC  
METAL**

**DESCRIPTION**

ZOCO 104P is a pelleted version of ZOCO 104 for applications where properties such as free flow, low dusting and low bulk are required.

**USES**

Rubber

**TYPICAL TECHNICAL VALUES\*\***

<b>CHEMICAL PROPERTIES (%)</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Zinc Oxide (ZnO)		99.9	99.99
Lead (Pb)	0.0024		0.0015
Cadmium (Cd)	0.0010		0.0003
Copper (Cu)	0.0005		0.0001
Iron (Fe)	0.0005		0.0002
Loss at 100 C	0.15		0.05
<b>PHYSICAL PROPERTIES</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Surface Area (m <sup>2</sup> /g)	6.00	4.00	5.00
Screen Test %		- 100 Mesh	50
Bulk Density (lb/cu. ft)		75	85
Specifications	ASTM D-79		

**\*\* The above specifications are typical for the noted grade. Zochem will produce material to meet specific customer specifications.**

REVISION 07: Jan. 21, 2010