



**ZOCHEM INC.**

A SUBSIDIARY OF HUBBAY MINERALS INC.

P.O. BOX 1120  
BRAMPTON, ONTARIO, CANADA L6V 2L8

PH: 800 324-1806  
PH: 905 453-4100

**ZOCO 101** **ZOCHEM ZINC OXIDE**

**FRENCH PROCESS ZINC OXIDE**  
**PRODUCED FROM PRIMARY GRADE ZINC**

**DESCRIPTION**

ZOCO 101 is a fine particle size, high purity, zinc oxide excellent for applications requiring higher reactivity to the ZOCO 100 and good suspension.

**USES**

Rubber, Paint, Chemicals, Stearates, Resins, Primers, Adhesives

**TYPICAL TECHNICAL VALUES\*\***

<b>CHEMICAL PROPERTIES (%)</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Zinc Oxide (ignited basis)		99.9	99.9
Lead (Pb)	0.0024		0.0015
Cadmium (Cd)	0.0010		0.0003
Copper (Cu)	0.0005		0.0001
Iron (Fe)	0.0005		0.0002
Loss at 100 C	0.15		0.05
<b>PHYSICAL PROPERTIES</b>	<b>MAXIMUM</b>	<b>MINIMUM</b>	<b>TYPICAL</b>
Surface Area (m <sup>2</sup> /g)	7.99	6.50	7.40
Particle Size (microns)	0.16	0.13	0.14
Bulk Density (lb/cu. ft)			50
Apparent Density (lb/cu.ft)			18
Screen Test - Through 325 Mesh (%)		99.90	99.95
Specifications			ASTM D-79

**\*\* The above specifications are typical for the noted grade. Zochem will produce material to meet specific customer specifications.**

REVISION 07: January 19, 2010